

3 Gang WiFi Switch



- » Size: 85mm×85×32mm
- » Item no: L6-HS3
- » Weight: 0.3kg
- » Packing box size: 141mm×103×47mm
- » Panel: Tempered Crystal Glass
- » Bottom Materials: Retardant PC
- » Rated voltage: AC 100-250V 50/60Hz
- » Rated current/Max Current: 3A/10A
- » Rated Load: 200W
- » Load type: Incandescent lamp, energy saving lamp, fluorescent
- » Wireless Wi-Fi standard: 802.11b/g/n
- » Wireless Wi-Fi Security: WEP/WPA/WPA2(AES-TKIP-Personal)
- » Wi-Fi performance Transmission power: +20dBm,11Mbps(CCK)
- » Wi-Fi performance Receiver sensitivity: -89dBm,11Mbps(CCK)W
- » Standby Current: 0.001A
- » Standby power: 0.25W
- » Operating temperature: -25 degree to +60 degree
- » Relative humidity:<95%

WIFI Curtain Switch



- » Size: 85mm×85×32mm
- » Item no: L6-HC
- » Weight: 0.3kg
- » Packing box size: 141mm×103×47mm
- » Panel: Tempered Crystal Glass
- » Bottom Materials: Retardant PC
- » Rated voltage: AC 100-250V 50/60Hz
- » Rated current/Max Current: 3A/10A
- » Rated Load: 200W
- » Load type: Incandescent lamp, energy saving lamp, fluorescent
- » Wireless Wi-Fi standard: 802.11b/g/n
- » Wireless Wi-Fi Security: WEP/WPA/WPA2(AES-TKIP-Personal)
- » Wi-Fi performance Transmission power: +20dBm,11Mbps(CCK)
- » Wi-Fi performance Receiver sensitivity: -89dBm,11Mbps(CCK)W
- » Standby Current: 0.001A
- » Standby power: 0.25W
- » Operating temperature: -25 degree to +60 degree
- » Relative humidity:<95%

WIFI LED Dimmer Switch



- » Size: 85mm×85×32mm
- » Item no: L6-HD
- » Weight: 0.3kg
- » Packing box size: 141mm×103×47mm
- » Panel: Tempered Crystal Glass
- » Bottom Materials: Retardant PC
- » Rated voltage: AC 100-250V 50/60Hz
- » Rated current/Max Current: 3A/10A
- » Rated Load: 1-400W
- » Load type: Incandescent lamp, energy saving lamp, fluorescent
- » Wireless Wi-Fi standard: 802.11b/g/n
- » Wireless Wi-Fi Security: WEP/WPA/WPA2(AES-TKIP-Personal)
- » Wi-Fi performance Transmission power: +20dBm,11Mbps(CCK)
- » Wi-Fi performance Receiver sensitivity: -89dBm,11Mbps(CCK)W
- » Standby Current: 0.001A
- » Standby power: 0.25W
- » Operating temperature: -25 degree to +60 degree
- » Relative humidity:<95%

WIFI Relay Fan Switch



- » Size: 85mm×85×32mm
- » Item no: L6-HF
- » Weight: 0.3kg
- » Packing box size: 141mm×103×47mm
- » Panel: Tempered Crystal Glass
- » Bottom Materials: Retardant PC
- » Rated voltage: AC 100-250V 50/60Hz
- » Rated current/Max Current: 3A/10A
- » Rated Load: 200W
- » Load type: Incandescent lamp, energy saving lamp, fluorescent
- » Wireless Wi-Fi standard: 802.11b/g/n
- » Wireless Wi-Fi Security: WEP/WPA/WPA2(AES-TKIP-Personal)
- » Wi-Fi performance Transmission power: +20dBm,11Mbps(CCK)
- » Wi-Fi performance Receiver sensitivity: -89dBm,11Mbps(CCK)W
- » Standby Current: 0.001A
- » Standby power: 0.25W
- » Operating temperature: -25 degree to +60 degree
- » Relative humidity:<95%

WiFi Universal Socket



- » Size: 86mm×86×32mm
- » Item no: L5-H0R1-GWK(White) & L5-H0R1-GLK(Black)
- » Weight: 0.3kg
- » Packing box size: 141mm×103×47mm
- » Panel: Tempered Crystal Glass
- » Bottom Materials: Retardant PC
- » Rated voltage: AC 100-250V 50/60Hz
- » Rated current: 10A
- » Rated Load resistive: 1500W
- » Rated Load Inductive: 2000W
- » Wireless Wi-Fi standard: 802.11b/g/n
- » Wireless Wi-Fi Security: WEP/WPA/WPA2(AES-TKIP-Personal)
- » Wi-Fi performance Transmission power: + 20dBm, 11Mbps (CCK)
- » Wi-Fi performance Receiver sensitivity: -89dBm, 11Mbps(CCK)W
- » Standby Current: 0.001A
- » Standby Power: 0.25W
- » Relative humidity:<95%



WIFI IR Repeater

- » Size: 106mm×106×30mm
- » Item no: L5-HR
- » Weight: 0.3kg
- » Packing box size: 169mm×135×47mm
- » Input Voltage: AC 100-250V 50/60Hz
- » Input Power: 5VDC
- » RF Transmission: 38-36KHz
- » Wireless Wi-Fi standard: 802.11b/g/n
- » Wireless Wi-Fi Security: WEP/WPA/WPA2(AES-TKIP-Personal)
- » Wi-Fi performance Transmission power: + 20dBm, 11Mbps (CCK)
- » Wi-Fi performance Receiver sensitivity: -89dBm, 11Mbps(CCK)W
- » Standby Current: 0.001A
- » Standby Power: 0.25W
- » Operating temperature: -20 degree to +60 degree
- » Relative humidity:<80%